

Line GOLIA
SUPER PROFESSIONAL high pressure cleaners
Hot water



TECHNICAL FEATURES

The range **GOLIA** is built on a strong epoxy painted metal frame with a water cooled horizontal boiler for the pre-heating of the water and the partila decantino of the scale to grant an excellent working of the mahines

Cover in STAINLESS STEEL AISI 430

Available also with voltage at 60 HZ

Model	Pressure	Water dly	Engine power	Absor.power	Voltage
GOLIA 20/21	30-200 BAR	500-1260 lt/h	10	8,5 KW	TRI 230-400V 50 HZ
GOLIA 10/30	30-100 BAR	500-1800 lt/h	7,5 HP	6,5 KW	TRI 230-400V 50 HZ
GOLIA 20/30	30-200 BAR	500-1800 lt/h	15 HP	12.5 KW	TRI 230-400V 50 HZ

TECHNICAL DESCRIPTION – range GOLIA

- H.P. pump with 3 ceramic pistons on line
- Electrical motor 230-400 V – 50 HZ with 2 bearings and overload thermal protection
- Independent burner
- Horizontal boiler – water cooled
- Double coil in steel thick. ½” , tube 50 meter long
- Delayed start up of the boiler flame after 6 sec
- Fuel tank in the rear part with level indicator both electrical and visual. Large opening for fuelling and discharging.
- By pass valve with pressure adjuster
- Gauge meter
- Water tank complete with automatic float incorporated in the machine
- Thermostat for temperature adjustment from 30°C –100°C
- 24 volts electrical box
- Safety valve
- Transformer 400-230 – 24 Volt
- Delayed total stop adjustable from 0-30 sec
- Stop of burner for lack of fuel
- Inlet water filter
- Filter before the pump
- Fuel filter
- High pressure hose 10 mt – R2
- Service lance 120 cm with automatic gun
- Stainless steel water nozzle

- DIMENSIONS AND WEIGHT
- Length : cm 130
- Width : cm 62
- Height cm 100
- Weight kg 285

ON REQUEST

- Stop of the machine for lack of water