



High Pressure Cleaners

LASLO S.R.L.

Via Bergamo, 34/a
26029 Soncino (CR)
Tel. +39 0374 83207
Fax +39 0374 84264
idro@castello-srl.com
www.castello-srl.com

Range URANO

PROFESSIONAL High pressure cleaners

Hot water



URANO 304 and URANO 430



URANO PL



URANO X

TECHNICAL FEATURES

Line URANO BIG professional hot water Is built on a strong black epoxy painted frame, with 2 fixed and 2 pivoting wheels. It can be produced with different choice of covers: STAINLESS STEEL AISI 304 or AISI 430, in strong plastic, red or blue colour.

The version URANO X is built COMPLETELY IN STAINLESS STEEL (frame and cover)

It is available also the version URANO BIG, super professional (see the "URANO BIG" technical description.

Available also with voltage at 60 HZ

Model	Pressure	Water dly	Engine power	Absor.power	Voltage
URANO 12/10	30-120 BAR	300-600 lt/h	3 HP	3 KW	1-phase 230V-50 HZ
URANO 15/15	30-150 BAR	300-900 lt/h	5.5 HP	5 KW	TRI 230-400V 50 HZ
URANO 15/21	30-150 BAR	300-1260 lt/h	7.5 HP	6,5 KW	TRI 230-400V 50 HZ
URANO 20/15	30-200 BAR	300-900 lt/h	7,5 HP	6,5 KW	TRI 230-400V 50 HZ
URANO 20/21	30-200 BAR	300-1260 lt/h	10 HP	8,5 KW	TRI 230-400V 50 HZ

Laslo s.r.l.
C.F. e P.IVA 01464570199
REA CR 173789
Capitale Sociale Euro 12.000,00 i.v.a.

TECHNICAL DESCRIPTION range URANO

- H.P. pump with 3 ceramic pistons on line
- Electrical motor 230-400V with 2 bearings and overload thermal protection
- Vertical boiler with weldless double coil 3/8", bottom made of refractory cement
- Delayed start of 6 sec. of the burner spark
- Independent burner
- Flame control of the burner by photocell for the maximum safety standards
- Water tank with automatic float level
- Machine stop in case of micro-leakages
- Device on the control board to reduce pressure and water delivery
- Device on the control panel for the suction of the detergent on high pressure
- Thermostat regulation temperature 30°-100° C
- Temperature : 30°C – 100°C
- Nr. 3 pressure switches and 1 flow switch
- Safety valve
- Automatic stop of the machine if left idle for 30 min
- Electric panel at 24 volts complete of remote control switch and thermal overload
- Transformer 230-400-24 Volt
- Delayed total stop adjustable 0-30 sec
- Stop of burner for lack of fuel
- Anti-shock dumper standard on the model URANO 20/21, on request for the other models of the range
- Pressure gauge for pressure adjustment
- By pass valve
- Inlet water filter
- Water filter before the pump
- Detergent filter with no-return valve
- Fuel filter
- Fuel tank 23 lt
- Double steel plaited high pressure hose 10 mt
- Service lance of 120 cms with automatic gun
- Stainless steel water nozzle

ON REQUEST

- Antiscale device
- Stop of machine for lack of water
- Anti-shock dumper on request for the models up to 7,5 HP. Standard on model 20/21 – 10 HP
- Flexible joint between pump and motor on models 7.5HP